

# Flexible Hoses

# Flexible Hoses

FX



<b>DN</b> 6-8 6-8 6-8 8-10 8-10 13-15 13-15	<b>APPLICAZIONI</b> Rubinetti miscelatori Monofori Cassette di scarico Distributori automatici Rubinetti singoli Scaldabagni Idromassaggio	<b>APPLICATIONS</b> Mixer taps Single lever mixers Flush tanks Automatic distributors Single taps Water heaters Whirlpools	<b>UTILISATIONS</b> Mitigeurs Monotrou Boites de WC Distributeurs automatiques Robinets Chauffe-eau Hydro-massage	<b>APLICACIONES</b> Grifos mezcladores Grifos monoblock Descargas de agua Distribuidores automaticos Grifos Calentadores Hidromasaje
	<b>MATERIALI</b> Anima: EPDM Treccia: Acciaio inox AISI 304 (AX) Alluminio (AL) Raccordi : Ottone CW 614 N Bussole : Acciaio inox AISI 304 Ottone CW 614 N	<b>MATERIALS</b> Core: EPDM Braid: Stainless steel AISI 304 (AX) Aluminium (AL) Fittings: Brass CW 614 N Sleeves: Stainless steel AISI 304 Brass CW 614 N	<b>MATERIAUX</b> Tuyau: EPDM Tresse: Acier inox AISI 304 (AX) Aluminium (AL) Raccords: Laiton CW 614 N Douilles de sertissage: Acier inox AISI 304 Laiton CW 614 N	<b>MATERIALES</b> Tubo: EPDM Trenza: Acero inoxidable AISI 304 (AX) Aluminio (AL) Racores: Laton CW 614 N Capsulas de apriete: Acero inoxidable AISI 304 Laton CW 614 N

LUNGHEZZA FLESSIBILE DA 20 A 300 CM - FLEXIBLE HOSE LENGHT FROM 20 TO 300 CM - LONGUEUR DU TUYAU FLEXIBLE DE 20 À 300 CM - LONGITUD DEL FLEXIBLE DESDE 20 A 300 CM

	Working pressure	Max working temperature	Minimum bore	Minimum flow rate	Minimum bending radius
DN 6	10 bar	90°C	4,7 mm	15 l/min. (3bar)	25 mm
DN 8	10 bar	90°C	6,2 mm	26,3 l/min (3bar)	30 mm
DN 10	10 bar	90°C	7,2 mm	42,3 l/min. (3bar)	35 mm
DN 13	10 bar	90°C	9,5 mm	65,8 l/min. (3bar)	45 mm
DN 15	10 bar	90°C	12 mm		60 mm

DN 6	G 1/4 - G 3/8 G 1/2 M 15X1	G 3/8		G 1/4 - G 3/8 - G 1/2	G 1/4 - G 3/8	
DN 8	G 1/4 - G 3/8 G 1/2 - G 3/4	G 3/8	G 3/8	G 1/4 - G 3/8 G 1/2 - G 3/4	G 1/4 - G 3/8 G 1/2	G 3/8 - G 1/2
DN 10	G 3/8 - G 1/2 G 3/4	G 3/8	G 3/8 - G 1/2 G 3/4	G 3/8 - G 1/2 - G 3/4	G 3/8	G 3/8 - G 1/2 G 3/4
DN 13	G 3/8 - G 1/2 G 3/4	G 1/2	G 1/2 - G 3/4	G 3/8 - G 1/2 - G 3/4	G 1/2	G 1/2 - G 3/4
DN 15	G 1/2 - G 3/4			G 1/2 - G 3/4		



### FXE1



### FXE2



### FXE3



### FXE4



G 3/8		M8X1 L1=16mm. L2=44mm. M10X1 L1=18mm. L2=45mm.	d=8mm. L1=7mm. L2=25mm. d=10mm. L1=7mm. L2=25mm.	
G 3/8 - G 1/2 G 3/4	G 1/2	M10X1 L1=18mm. L2=45mm. M12X1 L1=18mm. L2=45mm.	d=8mm. L1=7mm. L2=25mm. d=10mm. L1=7mm. L2=25mm.	G 3/8 d=8,10,12mm.
G 3/8 - G 1/2 G 3/4	G 1/2	M10X1 L1=18mm.	d=10mm. L1=7mm. L2=25mm.	d=10,12,14,15mm.
G 3/8 - G 1/2 G 3/4			d=15mm. L1=10mm. L2=30mm.	d=15,22mm.
G 1/2 - G 3/4				

# Antivibranti

FXF



## APPLICAZIONI

Pompe  
Autoclavi  
Caldaie  
Depuratori  
Climatizzazione  
Impieghi industriali

## APPLICATIONS

Pumps  
Autoclaves  
Boilers  
Water softeners  
Air conditioning  
Industrial applications

## UTILISATIONS

Pompes  
Autoclaves  
Chaudières  
Epurateurs  
Climatisation  
Applications industrielles

## APLICACIONES

Bombas  
Autoclaves  
Calderas  
Depuradores  
Climatización  
Aplicaciones industriales

## MATERIALI

Anima: EPDM  
Treccia:  
Acciaio zincato (AC)  
Acciaio inox AISI 304 (AX)  
Raccordi:  
Ottone CW 614 N  
Bussole:  
Acciaio inox AISI 304 (AX)  
Alluminio 1050

## MATERIALS

Core: EPDM  
Braid:  
Galvanized steel (AC)  
Stainless steel AISI 304 (AX)  
Fittings:  
Brass CW 614 N  
Sleeves:  
Stainless steel AISI 304 (AX)  
Aluminium 1050

## MATERIAUX

Tuyau: EPDM  
Tresse:  
Acier galvanisé (AC)  
Acier inox AISI 304 (AX)  
Raccords:  
Laiton CW 614 N  
Douilles de sertissage:  
Acier inox AISI 304 (AX)  
Aluminium 1050



## MATERIALES

Tubo: EPDM  
Trenza:  
Acero galvanizado (AC)  
Acero inoxidable AISI 304 (AX)  
Racores :  
Laton CW 614 N  
Capsulas de apriete:  
Acero inoxidable AISI 304 (AX)  
Aluminio 1050

LUNGHEZZA FLESSIBILE DA 20 A 300 CM - FLEXIBLE HOSE LENGHT FROM 20 TO 300 CM - LONGUEUR DU TUYAU FLEXIBLE DE 20 À 300 CM - LONGITUD DEL FLEXIBLE DESDE 20 A 300 CM

## TECHNICAL DATA

	Working pressure	Max working temperature	Minimum bore	Minimum bending radius
DN 13	10 bar	90°C	9,5 mm	45 mm
DN 15	10 bar	90°C	12 mm	60 mm
DN 19	10 bar	90°C	14,7 mm	75 mm
DN 25	10 bar	90°C	20 mm	90 mm
DN 32	6 bar	90°C	26 mm	120 mm
DN 40	6 bar	90°C	32 mm	150 mm
DN 50	4 bar	90°C	41 mm	180 mm



DN 13	G 1/2 - G 3/4	G 1/2 - G 3/4	G 1/2 - G 3/4	G 1/2 - G 3/4
DN 15	G 1/2 - G 3/4	G 1/2 - G 3/4	G 1/2 - G 3/4	
DN 19	G 3/4 - G 1	G 3/4 - G 1	G 3/4 - G 1	G 3/4 - G 1
DN 25	G 1	G 1	G 1 - G 1 1/4	G 1
DN 32	G 1 1/4	G 1 1/4		
DN 40	G 1 1/2	G 1 1/2		
DN 50	G 2	G 2		

# Gas

## FXYP



### SERIE GAS

#### MATERIALI

Anima: PVC, SBR - NBR  
 Treccia: Acciaio zincato  
 Raccordi : Ottone CW 614 N  
 Bussole :  
 Alluminio 1050

### GAS SERIES

#### MATERIALS

Core: PVC, SBR - NBR  
 Braid: Galvanized steel  
 Fittings: Brass CW 614 N  
 Sleeves:  
 Aluminium 1050

### SERIE GAZ

#### MATERIAUX

Tuyau: PVC, SBR - NBR  
 Tresse: Acier galvanise  
 Raccords: Laiton CW 614 N  
 Douilles de sertissage:  
 Aluminium 1050

### SERIE GAS

#### MATERIALES

Tubo: PVC, SBR - NBR  
 Trenza: Acero galvanizado  
 Racores : Laton CW 614 N  
 Capsulas de apriete:  
 Aluminio 1050



Ø 8X13

G 1/4 - G 3/8  
 G 1/2 - G 3/4

G 1/4 - G 3/8  
 G 1/2 - G 3/4

G 1/4 - G 3/8  
 G 1/2 - G 3/4

Ø 13X20

G 3/8 - G 1/2  
 G 3/4

G 3/8 - G 1/2  
 G 3/4

G 3/8 - G 1/2  
 G 3/4

LUNGHEZZA FLESSIBILE DA 20 A 300 CM - FLEXIBLE HOSE LENGHT FROM 20 TO 300 CM - LONGUEUR DU TUYAU FLEXIBLE DE 20 À 300 CM - LONGITUD DEL FLEXIBLE DESDE 20 A 300 CM

### SERIE BRUCIATORI

#### MATERIALI

Anima: NBR  
 Treccia: Acciaio zincato  
 Raccordi : Acciaio 9SMnPb36 (AVP)  
 Bussole : Ferro

### BURNES SERIES

#### MATERIALS

Core: NBR  
 Braid: Galvanized steel  
 Fittings: Steel 9SMnPb36 (AVP)  
 Sleeves: Iron

### SERIE BRULEURS




#### MATERIAUX

Tuyau: NBR  
 Tresse: Acier galvanise  
 Raccords: Laiton 9SMnPb36 (AVP)  
 Douilles de sertissage: Fer

### SERIE QUEMADORES

#### MATERIALES

Tubo: NBR  
 Trenza: Acero galvanizado  
 Racores : Laton 9SMnPb36 (AVP)  
 Capsulas de apriete: Hierro



G 1/4 - G 3/8

G 1/4

G 1/4 - G 3/8