

# Antivibranti

FXF



## APPLICAZIONI

Pompe  
Autoclavi  
Caldaie  
Depuratori  
Climatizzazione  
Impieghi industriali

## APPLICATIONS

Pumps  
Autoclaves  
Boilers  
Water softeners  
Air conditioning  
Industrial applications

## UTILISATIONS

Pompes  
Autoclaves  
Chaudières  
Epurateurs  
Climatisation  
Applications industrielles

## APLICACIONES

Bombas  
Autoclaves  
Calderas  
Depuradores  
Climatización  
Aplicaciones industriales

## MATERIALI

Anima: EPDM  
Treccia:  
Acciaio zincato (AC)  
Acciaio inox AISI 304 (AX)  
Raccordi:  
Ottone CW 614 N  
Bussole:  
Acciaio inox AISI 304 (AX)  
Alluminio 1050

## MATERIALS

Core: EPDM  
Braid:  
Galvanized steel (AC)  
Stainless steel AISI 304 (AX)  
Fittings:  
Brass CW 614 N  
Sleeves:  
Stainless steel AISI 304 (AX)  
Aluminium 1050

## MATERIAUX

Tuyau: EPDM  
Tresse:  
Acier galvanisé (AC)  
Acier inox AISI 304 (AX)  
Raccords:  
Laiton CW 614 N  
Douilles de sertissage:  
Acier inox AISI 304 (AX)  
Aluminium 1050


## MATERIALES

Tubo: EPDM  
Trenza:  
Acero galvanizado (AC)  
Acero inoxidable AISI 304 (AX)  
Racores :  
Latón CW 614 N  
Capsulas de apriete:  
Acero inoxidable AISI 304 (AX)  
Aluminio 1050

LUNGHEZZA FLESSIBILE DA 20 A 300 CM - FLEXIBLE HOSE LENGHT FROM 20 TO 300 CM - LONGUEUR DU TUYAU FLEXIBLE DE 20 À 300 CM - LONGITUD DEL FLEXIBLE DESDE 20 A 300 CM

## TECHNICAL DATA

	Working pressure	Max working temperature	Minimum bore	Minimum bending radius
DN 13	10 bar	90°C	9,5 mm	45 mm
DN 15	10 bar	90°C	12 mm	60 mm
DN 19	10 bar	90°C	14,7 mm	75 mm
DN 25	10 bar	90°C	20 mm	90 mm
DN 32	6 bar	90°C	26 mm	120 mm
DN 40	6 bar	90°C	32 mm	150 mm
DN 50	4 bar	90°C	41 mm	180 mm



DN 13	G 1/2 - G 3/4	G 1/2 - G 3/4	G 1/2 - G 3/4	G 1/2 - G 3/4
DN 15	G 1/2 - G 3/4	G 1/2 - G 3/4	G 1/2 - G 3/4	G 1/2 - G 3/4
DN 19	G 3/4 - G1	G 3/4 - G1	G 3/4 - G1	G 3/4 - G1
DN 25	G 1	G 1	G 1 - G 1 1/4	G 1
DN 32	G 1 1/4	G 1 1/4		
DN 40	G 1 1/2	G 1 1/2		
DN 50	G 2	G 2		