

# Purificatori CLEANERS PURGEURS PURIFICADORES

Filtro ad uso domestico per il trattamento di acque potabili a PH neutro, di facile installazione su rubinetti esistenti e rimovibile.  
 Domestic filter suitable for treatment of drinking water with neutral pH. It mounts easily onto existing faucet and can be moved.  
 Filtre à usage domestique pour le traitement des eaux potables avec pH neutre. Facile à installer sur robinets existantes et amovible.  
 Filtro para uso doméstico para el tratamiento de agua potable de PH neutro. De fácil instalación sobre grifos existente y removible.

## WF117CW

### Caratteristiche tecniche:

Pressione max. d'esercizio 6 bar  
 Temperatura min/max. d'esercizio da 0°C a +30°C.  
 Testata in polipropilene  
 Vaso in SAN  
 Rubinetto con By-Pass in acciaio  
 Tubo ø 8mm, lunghezza 700 mm

### Technical features:

Max. working pressure 6 bar  
 Working temperature 0°C / +30°C  
 Polypropylene head  
 SAN bowl  
 Faucet with stainless steel By-Pass  
 Hose Ø 8mm, length 700mm

### Caractéristiques techniques:

Pression d'exercice maximale 6 bar  
 Température d'exercice min/max de 0°C à +30°C  
 Tête en polypropylène  
 Pot en SAN  
 Robinet avec by-pass en acier  
 Tuyau ø 8mm, longueur 700 mm

### Características técnicas:

Presión máx. de funcionamiento 6 bar  
 Temperatura mín/máx de funcionamiento de 0°C a +30°C  
 Cabezal de polipropileno  
 Recipiente de SAN  
 Grifo con by-pass de acero  
 Tubo ø 8mm, longitud 700 mm

WF117CW



Cartridge length	Dimensions L H	Flow rate L/h	Pieces per packing
9"¾	130 - 320	250	12

## CF9 CF9CW

Cartucce antibatteriche per WF117CW Antibacterial cartridges for WF117CW  
 Cartouches bactericides pour WF117CW Cartuchos antibacterianos para WF117CW

### Caratteristiche tecniche:

Carbone sinterizzato  
 Antibatterica  
 Portata 2 l/min (CF9)  
 Portata 6-8 l/min (CF9CW)  
 Temperatura max d'esercizio +28°C (CF9)  
 Per acqua fredda (CF9CW)

### Technical features:

Synterized activated carbon  
 Antibacterial  
 Flow rate 2l/min (CF9)  
 Flow rate 6-8l/min (CF9CW)  
 Max working temperature +28°C (CF9)  
 For cold water only (CF9CW)

### Caractéristiques techniques:


Charbon fritté  
 Bactéricide  
 Débit 2 l/min (CF9)  
 Débit 6-8 l/min (CF9CW)  
 Température d'exercice max +28° C (CF9)  
 Pour eau froide (CF9CW)

### Características técnicas:

Carbón sinterizado  
 Antibacteriano  
 Caudal 2 l/min (CF9)  
 Caudal 6-8 l/min (CF9CW)  
 Temperatura máx de funcionamiento +28°C (CF9)  
 Para agua fría (CF9CW)

CF9

CF9CW



Model	Micron	Dimensions
CF9	0,45	9"¾

Model	Micron	Dimensions
CF9cw	0,15	9"¾